Product Name: Cartridge for V BOARD MASTER S

# SAFETY DATA SHEET

Date of Issue: August 17, 2020

SDS No.: RI-115 Version: 004



Page 1/6

SDS No.:RI-115

# 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

For ink unless otherwise specified.

1.1. Product identifier

Product name : Cartridge for V BOARD MASTER S

Product code : WBS-VS-B/L

Mixture name : WMAM-B/L

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Ink for writing instrument

1.3. Details of the supplier of the safety data sheet

Name of manufacture

: PILOT CORPORATION OF EUROPE

/ supplier

Address : PAE de la Caille 74350 ALLONZIER-LA-CAILLE (France)

Telephone number : +33 (0)4 50 08 33 00

Working hours (from 8.30am to 12.30pm and from 01.30pm to 05.30pm

: 04.00pm on Friday-French time)

Facsimile number : +33 (0)4 50 46 43 59

E-mail address : pilotfrance@piloteurope.com

1.4. Emergency telephone number

Telephone number : +33 (0)1 45 42 59 59

Association / Organization : ORFILA / INRS <a href="http://www.centres-antipoison.net">http://www.centres-antipoison.net</a>

#### 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable Liquid Category 2 H225 Eye Damage / Eye Irritation Category 2 H319 Specific target organ toxicity (Single exposure) Category 3 H336

2.2. Label elements

Labeling according Regulation (EC) No 1272/2008

Hazard Pictograms



Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Product Name: Cartridge for V BOARD MASTER S

SDS No.:RI-115

Page 2/6

Precautionary statement(s)

Prevention

P102 Keep out of reach of children.

P210 Keep away from heat, hot surface, sparks, open flames and other ignition

sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

Response

P305 + P351 +P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

UFI number

WBS-VS-B UFI: NX5K-4Y2T-8D0C-RNP2 WBS-VS-L UFI: K46K-4YFK-VD0C-2AU6

2.3. Other hazards None

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS No.	EC No.	Index No.	REACH Registration No.	% Weight	Classification (EC)No 1272/2008	Component
Ethanol	64-17-5	200-578-6	603-002 -00-5	01-21194 57610-43 -xxxx	39-44	Flam Liq.2. H225	All colors
Propan-2-ol	67-63-0	200-661-7	603-117 -00-0	01-21194 57558-25 -xxxx	34-36	Flam Liq.2 H225 Eye lrrit. 2 H319 STOT SE 3 H336	All colors
Propan-1-ol	71-23-8	200-746-9	603-003 -00-0	-	2.9	Flam liq. 2 H225 Eye Dam.1 H318 STOT SE3 H336	Black
Carbon black	1333-86-4	215-609-9	Not applicable	-	4.0	Not classified	Black

H318: Causes serious eye damage.

# 4. FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation : Remove subject to ventilated fresh air. Consult physician if necessary.

Ingestion : Refer for medical attention.

Skin contact : Wash the affected area under tepid running water using a mild soap.

And refer for medical attention if irritation continues.

Eye contact : Gently rinse the affected eyes with clean water for at least 15 minutes.

And refer for medical attention if irritation continues.

Product Name: Cartridge for V BOARD MASTER S

SDS No.:RI-115

Page 3/6

First aid facilities : Ensure eyewash and water service are available.

4.2. Most important symptoms and effects, both acute and delayed

In case of skin or eye contamination treat as under First Aid Measures.

4.3. Indication of any immediate medical attention and special treatment needed There is no specific antidote. Treat symptoms.

#### 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media : In case of fire, use water spray, foam, dry, chemical powder

or carbon dioxide.

5.2. Special hazards arising from

the substance or mixture

: CO<sub>2</sub>, CO, NO<sub>x</sub>, and SO<sub>x</sub>, is produced after combustion.

5.3. Advice for firefighters : None

# 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

: Use proper ventilation. Use eye and skin protection.

6.2. Environmental precautions

: Do not dispose of waste to the sewer.

6.3. Methods and material for containment and cleaning up

: Absorb spill with material (cloth or paper), then place in a chemical waste containers.

6.4. Reference to other sections : None

#### 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

: Use proper ventilation.

Avoid rough handling or dropping.

Wear protective gloves / protective clothing /eye protection / face protection.

Keep out of reach of children and do not drink ink.

7.2. Conditions for safe storage, including any incompatibilities

: Store in a dry, cool, well-ventilated location.

7.3. Specific end use(s)

: Not use it except the ink for writing instruments.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1. Control parameters

Data of France.

	Limit value - Eight hours	Limit value - Short term	
Ethanol	1,000 ppm	5,000 ppm	
Propan-2-ol	_	400 ppm	
Carbon black	$3.5~\mathrm{mg/m^3}$	_	

#### 8.2. Exposure controls

: Wear protective gloves / protective clothing / eye protection / face protection.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

(a) Appearance : Black/Blue liquid (b) Odour : Alcohol odour

(c) Odour threshold : No data

(d) pH : Not applicable

(e) Melting point / Freezing point : No data

(f) Boiling point / boiling range : 78.3 degrees Celsius (Ethanol)
(g) Flash point : 14.0 degrees Celsius (Ethanol)

(h) Evaporation rate : No data
(i) Flammability (solid, gas) : Flammable

(j) Upper/lower flammability or : None

explosive limits

(k) Vapor pressure : 40hPa (at 20 degrees Celsius, Ethanol)
(l) Vapor density : 1.6 (at 20 degrees Celsius, Ethanol)
(m) Relative density : 0.82 - 0.84 (at 20 degrees Celsius)

(n) Solubility(ies)
(o) Partition coefficient: n-octanol / water
(p) Auto-ignition temperature
: Not applicable
: Not available
: No data

(q) Decomposition temperature : No data

(r) Viscosity : 6.0-13.0 mPa·s (at 20 degrees Celsius)

(s) Explosive properties : No data
(t) Oxidising properties : No data
9.2. Other information : None

# 10. STABILITY AND REACTIVITY

10.1. Reactivity : This material is stable.10.2. Chemical stability : This material is stable.

10.3. Possibility of hazardous reactions : This material is stable.

10.4. Conditions to avoid : Direct sunshine, the high temperature and

source of ignition.

10.5. Incompatible materials : Strong oxidizing agents and reducing

agents.

10.6. Hazardous decomposition products : Heating can release vapours which can be

ignited.

: Burning produces obnoxious and toxic

fumes, carbon oxides.

# 11. TOXICOLOGICAL INFORMATION

Mixture: No data

11.1. Information on toxicological effects

(a) acute toxicity Ethanol : LD<sub>50</sub> 11,500 mg/kg (rat oral)

Propan-2-ol : LD<sub>50</sub> 3,437 mg/kg (rat oral)

: LD<sub>50</sub> 4,059 mg/kg (rabbit skin)

Propan-1-ol :  $LD_{50}$  2,695 mg/kg (rat oral)

Product Name: Cartridge for V BOARD MASTER S SDS No.:RI-115 Page 5/6

(b) skin corrosion/ Ethanol : 400 mg open; MILD (rabbit skin) irritation Propan-2-ol : 500 mg open; MILD (rabbit skin)

Propan-1-ol : 500 mg open ; MILD (rabbit skin)

(c) serious eye damage/ Ethanol : 100 mg/24h; MODERATE

irritation (rabbit eye)

Propan-2-ol : 100 mg/24h; MODERATE

(rabbit eye)

Propan-1-ol : 100 mg/24h ; MODERATE

(rabbit eye)

(d) respiratory or skin No data available

sensitisation

(e) germ cell mutagenicity No data available

(f) carcinogenicity Carbon black : IARC Class 2B

(g) reproductive toxicity No data available

(h) STOT-single exposure Propan-2-ol : May cause drowsiness or dizziness.

Propan-1-ol : May cause drowsiness or dizziness.

(i) STOT-repeated exposure No data available (j) aspiration hazard No data available

Although carbon black is classified with 2B by IARC, it was in solution, and since it was not a granular material, it carried out the outside of classification.

# 12. ECOLOGICAL INFORMATION

Mixture: No data.

12.1. Toxicity Ethanol : LC<sub>50</sub> - Salmo gairdneri-13,000 mg/L-96H

EC<sub>50</sub> - Daphnia magna-12,340 mg/L-48H

Propan-2-ol : LC<sub>50</sub> - Fathead minnow- 11,130mg/L-96H

Propan-1-ol : EC<sub>50</sub> - Daphnia magna (Water flea)-

3,025 mg/L-48H

12.2. Persistence and No data available

degradability

12.3. Bioaccumulative No data available

potential

12.4. Mobility in soil12.5. Results of PBT andNo data availableNo data available

vPvB assessment

12.6. Other adverse effects No data available

# 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

· Follow all regulations in your country.

# 14. TRANSPORT INFORMATION

14.1. UN number : 1993

14.2. UN proper shipping name : Flammable liquid N.O.S (Ethanol)

Product Name: Cartridge for V BOARD MASTER S SDS No.:RI-115 Page 6/6

14.3. Transport hazard class(es) : 3 14.4. Packing group : II

14.5. Environmental hazards
14.6. Special precautions for user
14.7. Transport in bulk according to Annex II of
Not applicable.
Not applicable.

MARPOL 73/78 and the IBC Code

# 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Follow all regulations in your country.
- 15.2. Chemical safety assessment
  - · No data

# 16. OTHER INFORMATION

EU Hazard statement according to (EC) No 1272/2008

**Precautionary Statements** 

Prevention	P233	Keep container tightly closed.		
	P240	Ground and bond container and receiving equipment.		
	P241	Use explosion-proof electrical, ventilating and lighting equipment.		
	P242	Use non-sparking tools.		
	P243 Take action to prevent static discharges.			
	P280	Wear protective gloves/protective clothing/eye protection/face protection.		
	P264	Wash hands thoroughly after handling.		
	P261	Avoid breathing mist or vapours or spray.		
Response	P303+P361	IF ON SKIN (or hair): Take off immediately all		
	+P353	contaminated clothing. Rinse affected areas with water.		
	P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
	P337+P317	If eye irritation persists: Get medical help		
	P319	Get medical help if you feel unwell.		
	P370 + P378	In case of fire: Use water spray, foam, dry chemical powder or carbon dioxide to extinguish.		
Storage	P403+P235	Store in a well-ventilated place. Keep cool.		
	P403+P233	Store in a well-ventilated place. Keep container tightly closed.		
	P405	Store locked up.		
Disposal	P501	Dispose of contents and container in accordance with all		
		local, regional, national and international regulations.		

The information here is given in good faith, but no warranty, express or implied, is made. Final determination of suitability of any material is the sole responsibility of the user.